



ARCHITECTURAL SPECIFICATIONS GUIDELINES

PART 1 GENERAL

1.01 THIS SECTION INCLUDES

- A. Flooring and accessories as shown on the drawings and schedules and as indicated by the requirements of this section.

1.02 RELATED DOCUMENTS

- A. Drawings and General Provisions of the Contract (including General and Supplementary Conditions and Division 1 sections) apply to the work of this section.

1.03 RELATED SECTIONS

- A. Other Division 9 sections for floor finishes related to this section but not the work of this section.
- B. Division 3 Concrete; not the work of this section.
- C. Division 6 Wood and Plastics; not the work of this section.
- D. Division 7 Thermal and Moisture Protection; not the work of this section.

1.04 QUALITY ASSURANCE AND REGULATORY REQUIREMENTS

- A. Select an installer who is competent in the installation of Harbinger Acoustic vinyl click tile
- B. If required, provide resilient flooring and accessories supplied by one manufacturer, including leveling and patching compounds, and adhesives.

1.05 SUBMITTALS

- A. Submit shop drawings, seaming plan, coving details, and manufacturer's technical data, installation and maintenance instructions for flooring and accessories.
- B. Submit the manufacturer's standard samples showing the required colors for flooring and applicable accessories.
- C. If required, submit the manufacturer's certification that the flooring has been tested by an independent laboratory and complies with the required fire tests.

1.06 ENVIRONMENTAL CONDITIONS

- A. Deliver materials in good condition to the job site in the manufacturer's original unopened containers that bear the name and brand of the manufacturer, project identification, and shipping and handling instructions.
- B. Store materials in a clean, dry, enclosed space off the ground, and protected from the weather and from extremes of heat and cold. Store flooring in the spaces where they will be installed for at least 24 hours prior to installation.
- C. Maintain a constant temperature of 18C to 26C for a period of 24 hours prior to installation. This temperature should be maintained during installation, and for a 24 hour period after installation. Protect all materials from the direct flow of heat from hot-air registers, radiators, or other heating fixtures and appliances.
- D. Install flooring and accessories after the other finishing operations, including painting, have been completed. Close spaces to traffic during the installation of the flooring.

PART 2 PRODUCTS

2.01 RESILIENT FLOORING MATERIALS

- A. Harbinger **(Enter series, SKU, and Pattern description)**
- B. Harbinger Acoustic Click CompositeCore WPC and Click ERVP installed next to each other shall be in consecutive lot numbers.

2.02 ADHESIVES

- A. For general use, Harbinger Acoustic Click CompositeCore WPC and Click ERVP are normally loose laid without adhesive, although full spread gluing is also possible, if required and recommended in areas with heavy rolling loads. Manufacture



recommends Harbinger S900 wet-set adhesive.

PART 3 EXECUTION

3.01 INSPECTION

- A. All supporting surfaces shall be structurally sound, solid, stable, level, plumb and true to a tolerance in plane of 1/4" in 10 feet (6 mm in 3 m) for floors. Cracks and holes must be filled with a fast setting cement-based polymer modified patching compound or equivalent.
- B. Harbinger Acoustic Click CompositeCore WPC and Click ERVP can be installed on existing firm floors (Linoleum, PVC), but all textile floors must be removed. When laying the floor over existing ceramic tiles first level with fast setting cement-based polymer modified patching compound and PLANI/PATCH PLUS
- C. Failure to call attention to defects or imperfections will be construed as acceptance and approval of the subfloor. Installation indicates acceptance of substrates with regard to conditions existing at the time of installation.

3.02 PREPARATION

- A. Smooth concrete surfaces, removing rough areas, projections, ridges, and bumps, and filling low spots, control or construction joints, and other defects as recommended by the flooring manufacturer.
- B. Vacuum or broom-clean surfaces to be covered immediately before the application of flooring. Make subfloor free from dust, dirt, grease, and all foreign materials.

3.03 INSTALLATION

- A. Install flooring in strict accordance with the latest edition of "Harbinger Acoustic Click Installation Guide".
- B. Do not proceed with floor surface installation until all applicable site work, including substrate preparation, painting, equipment installation and other relevant work by trades affecting the installation area has been completed.
- C. Install flooring with tools and procedures in strict accordance with the manufacturer's written instructions.

3.04 CLEANING AND PROTECTION

- A. Cleaning: Perform the cleaning operations in accordance to the latest edition of "Harbinger Maintenance Guide".
- B. Protection: Protect the installed flooring against damage from rolling loads, other trades, or the placement of fixtures and furnishings. Refer to "Harbinger Acoustic Click Installation Guide" and "Harbinger Maintenance Guide".

END OF SECTION

These Architectural Specification Guidelines are intended for use by design and specification professionals as a template aid to specify and describe Harbinger products as part of the written Specifications component of Construction Contract Documents.

The data contained in this document is accurate as of the date of publication. Updates and revisions may have been made since this date. If verification is needed that this data is still current, please contact Harbinger at 1-866-646-6519.